Plate compactor

C60 Heavy duty

High Efficiency Compaction Capability:Utilizing advanced vibration technology, ensuring rapid and uniform compaction effects.
Durable and Robust Design:Constructed with high-strength materials, the machine is adaptable to various harsh working conditions and is designed for long-lasting durability.
Easy Operation:The user-friendly control interface allows operators to quickly master the machine, enhancing work efficiency.
Versatile Adaptability:Suitable for a variety of road materials, including soil, asphalt, and concrete, meeting the needs of different engineering projects.

Model	C60
Plate size	550*370mm
Plate thickness	8mm
Power Option	Honda GX160 Robin EY20 Local 168/170 Diesel engine173
N.W.	65KGS
G.W.	6 9KGS(Carton) 77KGS(Wooden case)
Machine dimension	800*400*650mm
Carton package dimension	800*400*650mm
Wooden case package dimension	820*430*760mm
Compaction depth	25cm
Walking speed	4-22m/min
Fuel tank capacity	According to the Engine standards
Quick-wear parts	Clutch, Exhaust pipe, Rubber block, Throttle switch, Air
Belt model	filter B-type 686mm / 1 pcs
Clutch size	φ115mm
Compacting force	15KN





Thickened plate
After heat treatment, high hardness, strong toughness, not easily broken or deformed



Strong Compacting force
Increase the exciter, 15KN Compacting force, without eccentricity, wear-resistant and high-temperature resistant



Belt cover
Prevents clutch and belt damage



Anti slip and shock-absorbing handle
Foldable shelf, multi angle adjustment

Plate compactor

C90 Heavy duty

High Efficiency Compaction Capability:Utilizing advanced vibration technology, ensuring rapid and uniform compaction effects.
Durable and Robust Design:Constructed with high-strength materials, the machine is adaptable to various harsh working conditions and is designed for long-lasting durability.
Easy Operation:The user-friendly control interface allows operators to quickly master the machine, enhancing work efficiency.
Versatile Adaptability:Suitable for a variety of road materials, including soil, asphalt, and concrete, meeting the needs of different engineering projects.

Model	C90
Plate size	570*420mm
Plate thickness	7mm
Power Option	Honda GX160 Robin EY20 Local 168/170 Diesel engine173
N.W.	68KGS
G.W.	8 1KGS(Wooden case)
Machine dimension	570*430*600mm
Wooden case package dimension	570*440*680mm
Compaction depth	25cm
Walking speed	4-20m/min
Fuel tank capacity	According to the Engine standards
Quick-wear parts	Clutch, Exhaust pipe, Rubber block, Throttle switch, Air
Belt model	filter A-type 650mm / 2 pcs
Clutch size	φ130mm
Compacting force	15KN





Thickened plate
After heat treatment, high hardness, strong toughness, not easily broken or deformed



Strong Compacting force
Increase the exciter, 15KN Compacting force, without eccentricity, wear-resistant and high-temperature resistant



Belt cover
Prevents clutch and belt damage



Anti slip and shock-absorbing handle
Foldable shelf, multi angle adjustment